



Material
Screw:M2.5, steel, Zinc plating
Wire protector:Stainless Steel
Terminal:Brass, Tin plating
Housing:PA66, UL94V-0

Electrical
Rated Voltage:300V
Rated Current:15A
Contact Resistance:20mΩ,
Insulation Resistance:500mΩ/DC500V
Withstand Voltage:AC2000V/1Min
Wire Range:24-14AWG 0.2-1.5mm²

Mechanical
Temp. Range:-40° C/+105° C
Max Soldering:+250° C 5Sec.
Torque:0.4Nm (3.54lb.in)
Strip Length:5.0-6.0mm

间距公差/Spacing tolerance (mm)				—		
0---5	6---12	13---24			0.1/10	
±0.15	±0.30	±0.50			±2°	
未注公差/General tolerances (mm)						
0---30	31---50	51---80	81---120		>121	
±0.30	±0.50	±0.70	±1.05		±1.20	

慈溪市禄普电子有限公司 CIXI LUPU ELECTRONICS CO., LTD.						PART NAME: LP301-5.00-NP		
LUPUOZ						DRAWING NO:		
STATUS	APPD	CHKD	DRFT	DATE	CUSTOM	PROJECT	UNITS	SCALE
	ZH			2022.6.9			MM	
TYPE: CUSTOMER DRAWINGS			REV	SIZE	SHEET			
			A	A4	1/1			